



Project	
Item #	
Quantity	

## **ARSHP HOT PLATE**

ARSHP-24-2 ARSHP-12-2

ARSHP-36-3 ARSHP-24-4

ARSHP-48-4 ARSHP-36-6

ARSHP-48-8 **ARSHP-60-10** 

#### STANDARD FEATURES

- Two piece lift off 32,000 BTU/hr. burners
- Heavy duty removable, 12" x 12" cast-iron grates
- Manual gas control valve for each burner
- Stainless steel pilots for instant ignition on each burner
- Full-width removable stainless steel crumb tray for easy cleaning
- 4" adjustable inset legs (12" to 48" models)
- Die-cast, red control knob
- Available in several widths from 12", 24", 36", 48", and 60"
- 4" back riser
- Two year limited warranty, parts, and labor

#### **OPTIONAL FEATURES**

- Stainless steel stands
- Casters for stands

NATURAL



Model Shown ARSHP-36-6

**GAS TYPE:** 

#### **DESCRIPTION**

**American Range ARSHP Series Hot Plate** 

Gas Hot Plate American Range No. ARSHP series comes in a variety of burner configurations single depth or double depth. Low profile gas hot plate. Stainless steel front, sides and front top ledge. 10" cooking height on 4" legs. 32,000 BTU/hr. open burners with lift off heads. Cast iron top grates. Full width stainless steel crumb trays and 6" back riser. One infinite heat control valve for each burner. Standing pilot ignition system. 3/4" rear gas connection Natural gas or LP.











# ARSHP HOT PLATES


TOP





**FRONT** 



SIDE







COUNTERTOP	BURNERS	WIDTH (MM)	DEPTH (MM)	HEIGHT (MM)	BTU	LBS
ARSHP12-2	2	12" (305)	30" (762)	10" (254)	64,000	95
ARSHP24-2	2	24" (610)	18" (458)	10" (254)	64,000	95
ARSHP 24-4	4	24" (610)	30" (762)	10" (254)	128,000	145
ARSHP-36-3	3	36" (914)	18" (458)	10" (254)	96,000	115
ARSHP-36-6	6	36" (914)	30" (762)	10" (254)	192,000	210
ARSHP-48-4	4	48" (1219)	18" (458)	10" (254)	128,000	140
ARSHP-48-8	8	48" (1219)	30" (762)	10" (254)	256,000	270
ARSHP 60-10	10	60" (1524)	30" (762)	10" (254)	320,000	325

MANIFOLD PRESSURE NATURAL GAS   PROPANE GAS   MANIFOLD SIZE					
5.0" W.C.	10.0" W.C.	3/4" (19MM)			

- Specify type of gas and altitude if over 2000 feet.
- · Please specify gas type when ordering.

NMFCCODE 25970-2 Class. 85

\*Shipping weight includes packaging and is approximate.

### Installation

- Combustible wall clearance
   For use only on non-combustible floors. Legs or casters are
   required, or 2" (51) overhang is required when curb mounted.
   Clearance from non-combustible walls is 0". When unit is placed
   next to combustible walls, clearances must exceed 12" (305) from
   sides, and 4" (102) from rear. Radiant broilers for non-combustible
   locations only.
- Commercial cooking equipment requires an adequate ventilation system. For additional information, refer to the National Fire Protection Association's standard.
- NFPA96 "Vapor Removal from Cooking Equipment." (NOTE: For North America only)

American Range is a quality manufacturer of commercial cooking equipment.

Because of continuing product improvements, these specifications are subject to change without prior notice.





